# Jain PVC Foot Valve®

A Real Pump Guard



### **Features & Benefits**


Compact Design

Innovative design manufactured from high performance rigid PVC compound



# **Unique Design of Strainer**

Unique design of strainer effectively screens trash and ensures minimum obstruction to



Positive shut off prevents leakage & avoids repeated priming of the pump.





# Precise Weight for Rubber

For Rubber seal precise weight given for quick seal

# Jain PVC Foot Valve®


#### **Additional Features:**

- Excellent chemical and corrosion resistance
- Light weight, no extra weight on suction pipe.
- 'K' value (friction coefficient of the valve) less than 0.8 ensures low frictional loss.
- Energy savings up to 30%
- Available in sizes of 2½", 3.0" and 4.0" BSPT/NPT female threaded connections (65, 80 & 100 mm)

## **Application**


Maintains water column in suction pipe of the pump

## **List of Spares**



SI.	Description	Material	
1	Body	PVC	
2	Nut & Bolt	Mild Steel	
3	Weight	Cast Iron	
4	Rubber Flap	Nitrile	
5	Washer	Mild Steel	
6	Flange	PVC	
7	Strainer	Nylon	

# **Dimensional Specification**



Size	D	W	Н	L
inch	mm	mm	mm	mm
2½"	65.00	130.00	148.00	23.00
3″	80.00	153.00	185.00	23.00
4"	100.00	200.00	206.00	30.00

# **Ordering Specifications**

JFV	XX	XXX
	Size, inch	Type of Connection
	212 - 2½" 300 - 3" 400 - 4"	BTF - BSPT female threaded NPF - NPT female threaded

Example: JFV212BTF - This code represents Jain PVC Foot Valves® of size 2½" with BSPT female threaded connection.



